

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1. (Currently Amended) An automatic level controlling apparatus for supporting an appliance, comprising:
 - a hollow leg body;
 - a piston inserted in the hollow leg body;
 - a spring seated on an upper portion of the piston;
 - a cap disposed on an upper portion of the piston to support an upper portion of the springleg body;
 - a frictional member disposed around the piston; and
 - a piston rod coupled to the piston and supported on a floor,

wherein the piston and the leg body has a first operation mode where the piston and the leg body are capable of relatively rotating and a second operation mode where the piston and the leg body cannot relatively rotate.
2. (Previously Presented) The automatic level controlling apparatus according to claim 1, wherein the frictional member is formed in a strip-shaped strip.
3. (Previously Presented) The automatic level controlling apparatus according to claim 1, wherein a lower portion of the leg body is supported on the appliance.

4. (Original) The automatic level controlling apparatus according to claim 1, wherein frictional member is formed of felt.
5. (Original) The automatic level controlling apparatus according to claim 1, wherein the piston rod is provided at an outer surface with a tightening portion supporting the appliance upward.
6. (Original) The automatic level controlling apparatus according to claim 1, wherein the cap is fixed on the leg body.
7. (Original) The automatic level controlling apparatus according to claim 1, wherein the piston rod and the piston are coupled to each other not to relatively rotate.
8. (Canceled)
9. (Previously Presented) The automatic level controlling apparatus according to claim 1, wherein the piston is provided at an outer surface with a seating groove in which the frictional member is disposed.
10. (Original) The automatic level controlling apparatus according to claim 1, wherein a relative rotation locking unit is formed between the piston and the leg body.

11. (Original) The automatic level controlling apparatus according to claim 10, wherein the relative rotation locking unit includes a projection formed on one of the piston and leg body and a groove formed on the other of the piston and leg body.

12. (Original) The automatic level controlling apparatus according to claim 1, wherein the relative rotation locking unit is formed on a lower portion of the piston.

13. (Original) The automatic level controlling apparatus according to claim 1, wherein a space for receiving the spring is formed below the cap.

14. (Previously Presented) An automatic level controlling apparatus for supporting an appliance, comprising:

a hollow leg body;

at least one hook projection extending upward from a bottom of the leg body;

a cap disposed on an upper portion of the leg body;

a piston inserted in the hollow leg body;

at least one hook step extending downward from a bottom of the piston;

a spring seated on an upper portion of the piston; and

a piston rod coupled by penetrating a center of the piston and supported on a floor.

15. (Original) The automatic level controlling apparatus according to claim 14, wherein the hook step is formed in a radial direction from the center of the piston.

16. (Original) The automatic level controlling apparatus according to claim 14, wherein the piston includes hook steps and hook grooves formed between the hook steps and the hook projection is engaged with the hook groove.

17. (Canceled)

18. (Previously Presented) An automatic level controlling apparatus for supporting an appliance, comprising:

a hollow leg body;

a cap disposed on an upper portion of the leg body;

a piston inserted in the leg body to be capable of vertically moving;

a piston rod coupled by penetrating a center of the piston and supported on a floor;

a spring extending from an upper portion of the piston to a lower portion of the cap to provide force moving the lower portion of the piston to the lower portion of the leg body in a state where there is no outer force; and

a relative rotation locking unit to prevent the piston from relatively rotating on the leg body when the lower portion of the piston contacts the lower portion of the leg body.

19. (Previously Presented) The automatic level controlling apparatus according to claim 18, further comprising a frictional member disposed around the piston and contacting the leg body.

20. (Currently Amended) An automatic level controlling apparatus for supporting an appliance, comprising:

a hollow leg body;

a piston inserted in the leg body to be capable of vertically moving;

a spring seated on an upper portion of the piston;

a cap disposed on an upper portion of the piston to support an upper portion of the spring
leg body;

a frictional member disposed around the piston and moving with the piston;

a seating groove provided at an outer circumference of the piston to receive the frictional
member;

a piston rod coupled to the piston and supported on a floor; and

a relative rotation locking unit formed between the piston and the leg body to prevent the
piston from relatively rotating on the leg body.